








































GUIDA ALLA SCELTA UTENSILI PNEUMATICI

GAMMA AVVITATORI










■	ARTICOLO	CODICE	MATERIALE	 max. Nm	 db (A) LpA	 db (A) LpW	 l/min.	 kg	MECCANISMO	 m/s ²
3/8"		1924F	Alluminio	108	93.6	104.6	59	0,5	Doppio martello	6.85
3/8"		1924B	Alluminio	353	91	95	80	1,5	Pin clutch	7.9
3/8"		1924CD	Composito	410	91.7	102.7	79	1,3	Doppio martello	6.2
1/2"		1927AN	Alluminio	244	89.4	100.4	190	2,1	Singolo martello	8.63
1/2"		1927G	Alluminio	325	92.2	103.2	113	1,2	Singolo martello	9.96
1/2"		1927B	Alluminio	705	98.0	109.0	133	2,1	Pin clutch	14.08
1/2"		1927XM	Alluminio	770	102	113	122	1,3	Singolo martello	7.5
1/2"		1927CD	Composito	1.020	95.5	106.5	130	2,3	Doppio martello	7.2
1/2"		1927P	Composito	1.750	95.1	106.1	290	2,0	Doppio martello	6.7
3/4"		1928XM	Alluminio	1.600	91.8	102.8	175	2,9	Doppio martello	12.96
3/4"		1928DA	Alluminio	1.695	96	99.5	300	4,3	Doppio martello	3.6
3/4"		1928DAL	Alluminio	1.695	96	99.5	300	4,8	Doppio martello	3.6
3/4"		1928CD	Composito	1.800	97.5	108.5	215	3,5	Doppio martello	11.4
1"		1930CD	Composito	2.445	95.6	97.1	410	7,1	Doppio martello	3,6
1"		1930PA	Alluminio	2.445	96.0	97.1	410	9,6	Doppio martello	7,2
1"		1930A	Alluminio	2.445	103.3	114.3	460	9,5	Doppio martello	67
1"		1930LH	Alluminio	2.441	97.1	108.1	282	7,1	Doppio martello	17.4
1"		1930LA	Alluminio	2.445	95.6	97.1	460	10,6	Doppio martello	3,6
1"		1930HLA	Alluminio	3.661	99	101	460	16,4	Doppio martello	16,4
1 1/2"		1930ZL	Alluminio	4.068	102.4	113.4	480	15	Doppio martello	69.6

GUIDA ALLA SCELTA UTENSILI PNEUMATICI

GAMMA AVVITATORI A CRICCHETTO

■	ARTICOLO	CODICE	 max. Nm	 db (A) LpA	 db (A) LpW	 l/min.	 kg	 m/s ²
1/4"		1921B1	24	96	85	90	0,4	2.6
1/4"		1921M1	27	84	88	96	0,6	1.8
1/4"		1922P1	68	90.6	101.6	88	0,6	8.61
3/8"		1921M2	27	84	88	96	0,6	1.8
3/8"		1922P2	68	90.6	101.6	88	0,6	8.61
1/2"		1921N3	68	80	87	140	1,2	2.6
1/2"		1922P3	136	94.9	105.9	113	1,5	18.28

GAMMA SMERIGLIATRICI

	ARTICOLO	CODICE	POTENZA	 db (A) LpA	 db (A) LpW	 l/min.	 kg	 m/s ²
		1933	0,20 kW	80.0	87.0	230	0,38	4.53
		1933L	0,20 kW	80.0	87.0	270	0,67	1.15
		1933AN90	0,20 kW	80.0	87.0	230	0,51	1.24
		1933I	0,38 kW	80.0	87.0	260	0,67	4.53
		1933IL	0,38 kW	79.0	97.0	113	1,4	1.6
		1933IH	0,75 kW	88.1	99.1	370	0,8	2.6
		1933ILH	0,75 kW	85.7	96.7	370	1,2	1.4
		1933AN90-H	0,75 kW	85.6	96.6	370	1,1	6.7
		1934MAV	0,04 kW	71	76	115	0,2	2.5
		1934MAV70	0,08 kW	80	87	115	0,2	4