

1256/C36-2

microdestornillador bimaterial con 36 puntas intercambiables de 4 mm y prolongación magnética


📏 200 g

📏 130x60x35 mm - 📏 200 g

para trabajos de precisión

En envase compacto de aluminio anodizado

art.	art.	
012560100	1256/C36-2	TX ☉ T3-T4-T5-T6-T7-T8-T9-T10-T15 RTX ☉ T6-T7-T8-T9-T10 PE ○ 0,7-0,9-1,3-1,5-2,0-2,5 mm LP ● 0,8-1,2-1,5-1,8-2,0-2,5-3,0-3,5-4,0 mm PH ☉ PH000-PH00-PH0-PH1 PZ ☉ PZ000-PZ00-PZ0-PZ1



- n. **1256TX:** ☉ T3 - T4 - T5 - T6 - T7 T8 - T9 - T10 - T15
- n. **1256RTX:** ☉ T6 - T7 - T8 - T9 - T10
- n. **1256LP:** ● 0,8 - 1,2 - 1,5 - 1,8 - 2 - 2,5 3 - 3,5 - 4 mm
- n. **1256PE:** ○ 0,7 - 0,9 - 1,3 - 1,5 - 2 mm
- n. **1256PH:** ☉ PH000 - PH00 - PH0 - PH1
- n. **1256PZ:** ☉ PZ000 - PZ00 - PZ0 - PZ1
- n. **1256/20:**
- n. **1256/30:**