

**1256/C36-2**
**Microschroevendraaier met 36 verwisselbare 4-mm bits en magnetisch verlengstuk**

□ 200 g


□ 130x60x35 mm - □ 200 g

Voor precisie werkzaamheden

In een compacte geanodiseerde aluminium box

012560100	Art.	
	1256/C36-2	TX ⊕ T3-T4-T5-T6-T7-T8-T9-T10-T15 RTX ⊕ T6-T7-T8-T9-T10 PE ○ 0.7-0.9-1.3-1.5-2.0-2.5 mm LP ● 0.8-1.2-1.5-1.8-2.0-2.5-3.0-3.5-4.0 mm PH ⊕ PH000-PH00-PH0-PH1 PZ ⊕ PZ000-PZ00-PZ0-PZ1

- n. **1256TX:** □ T3 - T4 - T5 - T6 - T7 T8 - T9 - T10 - T15
- n. **1256RTX:** □ T6 - T7 - T8 - T9 - T10
- n. **1256LP:** inzetstukken 4 mm voor schroeven met sleufkop □ 0,8 - 1,2 - 1,5 - 1,8 - 2 - 2,5 3 - 3,5 - 4 mm
- n. **1256PE:** □ 0,7 - 0,9 - 1,3 - 1,5 - 2 mm
- n. **1256PH:** □ PH000 - PH00 - PH0 - PH1
- n. **1256PZ:** □ PZ000 - PZ00 - PZ0 - PZ1
- n. **1256/20:**
- n. **1256/30:**



**Scan de QR-code om toegang te krijgen tot het**  
 Specificaties, media en documentatie in één klik.

