

1290
screwdrivers for slotted head screws

ISO 2380
Features:

- New bi-material handle with hard polypropylene core injected onto blade for improved fixing safety.
- Soft thermoplastic rubber coating.
- Chrome-plating free tip for perfect screw coupling, protected from oxidation with phosphate-coating treatment.



Betamax
MAXIMUM PERFORMANCE


	art.	SxAxL mm	L1 mm	Ø mm	g
012900003	1290 2,5X50	0,4x2,5x50	146	2,5	32,6
012900006	1290 2,5X75	0,4x2,5x75	171	2,5	33,6
012900009	1290 3X75	0,5x3x75	171	3,0	41
012900012	1290 3X100	0,5x3x100	196	3,0	36,8
012900018	1290 3,5X75	0,6x3,5x75	171	3,5	37,6
012900021	1290 3,5X100	0,6x3,5x100	196	3,5	39,3
012900030	1290 4X100	0,8x4x100	196	4,0	42,4
012900033	1290 4X125	0,8x4x125	221	4,0	44,7
012900036	1290 4X150	0,8x4x150	246	4,0	47,1
012900039	1290 5,5X100	1x5,5x100	209	5,0	62,5
012900042	1290 5,5X150	1x5,5x150	259	5,0	70,4
012900048	1290 6,5X100	1,2x6,5x100	220	6,0	87,3
012900051	1290 6,5X150	1,2x6,5x150	270	6,0	97,8
012900057	1290 8X150	1,2x8x150	282	7,0	132
012900060	1290 8X200	1,2x8x200	332	7,0	147,3
012900066	1290 10X200	1,6x10x200	332	8,0	168,3
012900069	1290 12X250	2x12x250	382	10	256,5