

BETA 1498/AT500

Battery charger / starter, 12/24 V



Certifications and Standards



SAFETY

Thanks to the numerous controls on the electronic board and the CPS system, starting is only guaranteed under optimal conditions, protecting battery and vehicle from faults and overcurrents, offering maximum peace of mind during use

HIGH PERFORMANCE

These chargers, designed with high quality components and following strict standards, guarantee exceptional performance and unrivalled reliability

VERSATILE

Convenience and versatility in a single device. Perfect for charging and starting your vehicle quickly, it guarantees efficiency and reliability in every situation



VOLTAGE UNDER CONTROL
Ammeter and switches integrated on the front panel allow continuous and precise monitoring of the charging voltage



SAFE VENTILATION
Large air intakes ensure constant air flow, preventing the instrument from overheating and guaranteeing long-lasting performance



QUALITY COMPONENTS
Large cable cross-sections and high-quality clamps ensure efficient current transfer even under high loads


Certifications and Standards



Specifications

POWER SUPPLY:	230 (1ph) V
FREQUENCY:	50/60 Hz
POWER:	890 W
VOLTAGE:	12/24 V
BATTERY TYPE:	Pb
MAXIMUM CURRENT:	37 A
CHARGING CURRENT:	30 A
CHARGING CAPACITY:	540 Ah 15h
POWER SUPPLY:	N/A
CHARGING POSITIONS:	6 + boost

Coded items

	Art.	L mm	P mm	H mm
014980761	1498/AT500	250	345	280

Scan the QR Code to access the web tab

Specs, media and documentation in one click.

