

## BETA 1498/PR25 Conventional battery charger, 6/12/24 V



### Certifications and Standards



#### ROBUSTNESS

Thanks to the robust metal case and high-quality components, these battery chargers are the perfect ally for every work situation, guaranteeing resistance and reliability in all conditions

#### SAFETY

The automatic thermal protections of these conventional battery chargers guarantee exceptional safety and reliability for the operator, offering maximum peace of mind during use

#### FUNCTIONAL

The voltage and charging speed selectors allow you to customise the settings to your specific needs, giving you complete control and optimal charging for every situation.



#### TRANSPORTABILITY

Ergonomic handle on the upper side facilitates carrying of the instrument



#### SAFE VENTILATION

Large air intakes ensure constant air flow, preventing the instrument from overheating and guaranteeing long-lasting performance



#### VOLTAGE UNDER CONTROL

The integrated ammeter on the front panel allows continuous and precise monitoring of the charging voltage


## Certifications and Standards



### Specifications

POWER SUPPLY:	230 (1ph) V
FREQUENCY:	50/60 Hz
POWER:	620 W
VOLTAGE:	6/12/24 V
BATTERY TYPE:	Pb
MAXIMUM CURRENT:	25 A
CHARGING CURRENT:	17 A
CHARGING CAPACITY:	255 Ah 15h
POWER SUPPLY:	N/A
CHARGING POSITIONS:	6

### Coded items

	Art.	L mm	P mm	H mm
014980733	1498/PR25	250	245	435

**Scan the QR Code to access the web tab**

Specs, media and documentation in one click.

