

BETA 1498/RP380 Conventional battery charger / starter, 12/24 V



Certifications and Standards



ROBUSTNESS

Thanks to the robust metal case and high-quality components, these battery chargers are the perfect ally for every work situation, guaranteeing resistance and reliability in all conditions

SAFETY

The automatic thermal protections of these conventional battery chargers guarantee exceptional safety and reliability for the operator, offering maximum peace of mind during use

FUNCTIONAL

Voltage and charging speed selectors allow you to customise the settings to your specific needs, giving you complete control and optimal charging for every situation

VERSATILE

Convenience and versatility in a single device. Perfect for charging and starting your vehicle quickly, it guarantees efficiency and reliability in every situation



TRANSPORTABILITY

Ergonomic handle on the upper side facilitates carrying of the instrument



SAFE VENTILATION

Large air intakes ensure constant air flow, preventing the instrument from overheating and guaranteeing long-lasting performance



VOLTAGE UNDER CONTROL

The integrated ammeter on the front panel allows continuous and precise monitoring of the charging voltage


Certifications and Standards



Specifications

POWER SUPPLY:	230 (1ph) V
FREQUENCY:	50/60 Hz
POWER:	900 W
VOLTAGE:	12/24 V
BATTERY TYPE:	Pb
MAXIMUM CURRENT:	38 A
CHARGING CURRENT:	25 A
CHARGING CAPACITY:	270 Ah 15h
POWER SUPPLY:	N/A
CHARGING POSITIONS:	2 + boost

Coded items

	Art.	L mm	P mm	H mm
014980750	1498/RP380	220	235	335

Scan the QR Code to access the web tab

Specs, media and documentation in one click.

