

BETA 1498/SC341

Battery charger / starter, 12/24 V, wheeled

Professional chargers with wheeled starter: high power and excellent portability

Ergonomic handle and sturdy wheels, selector switches for slow or fast charging, integrated ammeter, thermostatic protection and internal fuse for maximum safety against short circuits and reverse polarity



Specifications

POWER SUPPLY:	230 (1ph) V
FREQUENCY:	50/60 Hz
POWER:	1080 W
VOLTAGE:	12/24 V
BATTERY TYPE:	Pb
MAXIMUM CURRENT:	45 A
CHARGING CURRENT:	30 A
CHARGING CAPACITY:	375 Ah 15h
POWER SUPPLY:	N/A
CHARGING POSITIONS:	3 + boost
Weight:	18,1



Certifications and Standards:



ROBUSTNESS

Thanks to the robust metal case and high-quality components, these battery chargers are the perfect ally for every work situation, guaranteeing resistance and reliability in all conditions

SAFETY

The automatic thermal protections of these conventional battery chargers guarantee exceptional safety and reliability for the operator, offering maximum peace of mind during use

VERSATILE

Convenience and versatility in a single device. Perfect for charging and starting your vehicle quickly, it guarantees efficiency and reliability in every situation

TRANSPORTABILITY

A robust and at the same time easily transportable tool, thanks to ultra-resistant solid wheels and a practical ergonomic handle



BETA 1498/SC341

Battery charger / starter, 12/24 V,
wheeled

Operational advantages and benefits



VOLTAGE UNDER CONTROL

Ammeter and switches integrated on the front panel allow continuous and precise monitoring of the charging voltage



VERSATILITY OF USE

Solid, ultra-strong wheels for easy handling on all types of terrain



SAFE VENTILATION

Large air intakes ensure constant air flow, preventing the instrument from overheating and guaranteeing long-lasting performance

Scan the QR Code to access the web tab

Specs, media and documentation in one click.



BETA 1498/SC341

Battery charger / starter, 12/24 V,
wheeled

Technical Specifications

Specifications

POWER SUPPLY:	230 (1ph) V
FREQUENCY:	50/60 Hz
POWER:	1080 W
VOLTAGE:	12/24 V
BATTERY TYPE:	Pb
MAXIMUM CURRENT:	45 A
CHARGING CURRENT:	30 A
CHARGING CAPACITY:	375 Ah 15h
POWER SUPPLY:	N/A
CHARGING POSITIONS:	3 + boost

Weight: 18,1

Certifications and Standards:



Coded items

	Art.	L mm	P mm	H mm
014980755	1498/SC341	260	395	770

Scan the QR Code to access the web tab

Specs, media and documentation in one click.

