

**1635-S**
**Closed end connector terminals, for free connections**

CE

Insulating housing: transparent polycarbonate UL94 V0  
 Conductive body: brass  
 Captive screw: galvanized steel  
 Self-extinguishing: EN60695-2-10 a 850°C, EN 60335-1:2002 +A2:2006,  
 EN60695-2-11  
 Working temperature: max. 85 °C  
 Degree of protection: IP20  
 Reference standards: EN60998-1: EN60998-2-1:2004



Stated prices are for individual 10-way bars. Minimum quantity: 10 pcs



art.	art.	mm <sup>2</sup>	mm <sup>2</sup>	L mm	L1 mm	S mm	N
<b>BM9961</b>	BM9961	35 25 16	35	43.5	26.1	49.4	2 2+3 2+4
<b>BM9960</b>	BM9960	25 16 10	25	36.3	22.5	41.9	2 2+3 2+4
<b>BM995</b>	BM995	16 10 6	16	31.8	18.8	32.2	2 2+3 2+4
<b>BM994</b>	BM994	10 6 4	10	26	14.7	26	2 2+3 2+4
<b>BM993</b>	BM993	6 4 2.5	6	22.5	11.8	23	2 2+3 2+4
<b>BM9924</b>	BM9924	4 2.5 1.5	4	21	10.3	20	2 2+3 2+4
<b>BM992</b>	BM992	2.5 1.5 1	2.5	17.5	9	18.2	2 2+3 2+4
<b>BM991</b>	BM991	1.5 1 0.75	1.5	15	7.5	14.5	2 2+3 2+4