

1760DGT
Digitale automotive multimeter

CE

TECHNISCHE SPECIFICATIES:

RPM (tachometer):

VOOR 2 EN 4 cilinder motoren

RPM4 600 - 4000 RPM

RPM4 600 - 12000 RPM (x10 RPM)

RPM2/DIS 300 - 4000 RPM

RPM2/DIS 300 - 6000 RPM (x10 RPM)

Contacthoek: 4-8 CYL

Spanning DC: 400mV-4/40/400/1000V

Spanning AC: 4/40/400/700V

Ampere DC: 40/400mA-4/20A

Ampere AC: 40/400mA-4/20A

Weerstand: 400Ω-4/40/400kΩ-4/40MΩ

Capaciteit: 40/400nF-4/40/100μF

Frequentie: 5/50/500Hz-50/500-10MHz

Arbeidstijd: 0.1 % - 99.9%

Gelijk en wisselstroom: 1 - 10ms

Diode test: Test stroom 0.3mA

Continuïteit: <150Ω - Test stroom <0.3mA

Scherm: Hoog-contrast, verlicht 4-digit LCD

Overvoltage: Category II 1000V

Automatisch uitschakeling: 30 minuten

Voeding: 1 9V batterij (meegeleverd)

Inductieve klem (meegeleverd)

2 sensoren (meegeleverd)

Zachte opbergtas (meegeleverd)

Gebruiksaanwijzing



	art.	 kg
017600005	1760DGT	1,1