

Belangrijkste kenmerken:

- 3 laden (435x210 mm), met geleiding op kogellagers:
- 1 lade, 50 mm hoog
- 2 laden, 70 mm hoog.
- Boven compartiment (505x250 mm)
- Centraal veiligheidsslot aan voorzijde.
- Handvatten op het deksel
- Inklapbare zijhandgrepen voor eenvoudig gebruik



22

42C 8-10-11-12-13-14-15-17-19 mm
1082CM $\pm$ 160 mm
1150CM $\pm$ 180 mm
1770A 9 mm
1770RL 10x



14	C988-48	150 mm
	C988-25	
	C988-42	175 mm
	C988AO	Ø 8"
	C988	Ø 44.5-55-65-75- 8-18-11-12-13-14 mm
	C988-20	50 mm
	C988-30L	100 mm

12	CR30V72	250mm
	CR30V79	
	CR30V22	250mm
	CR10V8F	□ 38°
	CR20A	0-13-4 15-21.5

119



988PICS/KS ○ 1.5-2.5-3-4-5-6-8-10 mm
1201E ● 2.5x90-3x75-4x100-5.5x125 mm
1201EN ● 4x30
1202E ● PH1x80-PH2x100
1202EN ● PH1x30 mm
1253 ● 3.5x300 mm

18

	1048C	250 mm
	1128BMXC	150 mm
	1370C	300 g
	1692/5	5 m