


412L
punte elicoidali cilindriche serie lunga in acciaio HSS rettificate brunite
DIN 340

 R ≤ 800 N/mm²
 HV 750÷820

|  | art. | ∅ mm | L mm | L1 mm | g |
|---|------------|---------|---------|----------|----|
| 004120232 | 412L 2,00 | 2,00 | 85 | 56 | 2 |
| 004120234 | 412L 2,50 | 2,50 | 95 | 62 | 3 |
| 004120236 | 412L 3,00 | 3,00 | 100 | 66 | 5 |
| 004120238 | 412L 3,50 | 3,50 | 112 | 73 | 7 |
| 004120240 | 412L 4,00 | 4,00 | 119 | 78 | 9 |
| 004120242 | 412L 4,50 | 4,50 | 126 | 82 | 12 |
| 004120244 | 412L 5,00 | 5,00 | 132 | 87 | 14 |
| 004120246 | 412L 5,50 | 5,50 | 139 | 91 | 19 |
| 004120248 | 412L 6,00 | 6,00 | 139 | 91 | 22 |
| 004120250 | 412L 6,50 | 6,50 | 148 | 97 | 30 |
| 004120252 | 412L 7,00 | 7,00 | 156 | 102 | 34 |
| 004120256 | 412L 8,00 | 8,00 | 165 | 109 | 46 |
| 004120260 | 412L 9,00 | 9,00 | 175 | 115 | 63 |
| 004120264 | 412L 10,00 | 10,00 | 184 | 121 | 77 |

