

42INOX-AS
Ringmaulschlüssel, aus Edelstahl

- Dünne Köpfe
- Hohe Korrosionsbeständigkeit
- verhindert Fremdrost
- optimale mechanische Eigenschaften
- Maße in Zoll

	art.		L mm	A mm	Ø mm	S1 mm	S2 mm	h mm
000420356	42INOX-AS 1/4	1/4x1/4	95	15,2	10,1	3,4	5,2	10
000420358	42INOX-AS 5/16	5/16x5/16	116	19,0	12,3	3,9	6,2	20
000420360	42INOX-AS 3/8	3/8x3/8	137	22,8	15,1	4,5	7,1	30
000420361	42INOX-AS 7/16	7/16x7/16	148	24,8	16,5	4,8	7,5	40
000420363	42INOX-AS 1/2	1/2x1/2	169	28,8	19,6	5,4	8,4	60
000420364	42INOX-AS 9/16	9/16x9/16	180	30,8	21,0	5,7	8,8	75
000420366	42INOX-AS 5/8	5/8x5/8	201	34,6	23,8	6,3	9,7	100
000420367	42INOX-AS 11/16	11/16x11/16	212	36,6	25,2	6,7	10,2	115
000420369	42INOX-AS 3/4	3/4x3/4	233	40,5	28,0	7,3	11,4	155
000420371	42INOX-AS 13/16	13/16x13/16	254	44,5	30,7	7,9	12,4	200
000420372	42INOX-AS 7/8	7/8x7/8	264	46,4	32,2	8,1	12,8	220
000420373	42INOX-AS 15/16	15/16x15/16	285	50,3	34,9	8,5	13,5	280

