


## HSS-Co 8%

- Voor het boren in metaal, hout, kunststof en kunstharsen

	Art.	Ø mm	Ø"	A	g
004500016	450 16	16	(5/8)	57	21
004500019	450 19	19	(3/4)	51	30
004500020	450 20	20	-	51	29
004500022	450 22	22	(7/8)	51	43
004500025	450 25	25	(1")	51	58
004500029	450 29	29	(1"1/8)	51	73
004500032	450 32	32	(1"1/4)	51	70
004500035	450 35	35	(1"3/8)	51	99
004500038	450 38	38	(1"1/2)	44	72
004500040	450 40	40	(1"9/16)	44	77
004500044	450 44	44	(1"3/4)	44	95
004500051	450 51	51	(2")	44	120
004500057	450 57	57	(2"1/4)	44	148
004500060	450 60	60	(2"3/8)	44	165
004500064	450 64	64	(2"1/2)	44	180
004500065	450 65	65	(2"9/16)	44	185
004500070	450 70	70	(2"3/4)	44	211
004500076	450 76	76	(3")	44	249
004500083	450 83	83	(3"1/4)	44	261
004500092	450 92	92	(3"5/8)	44	311
004500095	450 95	95	(3"3/4)	44	337
004500105	450 105	105	(4"1/8)	44	398
004500114	450 114	114	(4"1/2)	44	466



Scan de QR-code om toegang te krijgen tot het  
Specificaties, media en documentatie in één klik.

