



BETA 666 LBF.FT

ZERO-RESET click-type wrench, scale in lbf.ft



Certifications and Standards



UNI EN ISO 6789

Features

The torque wrench that does not need to be unloaded

ZERO-RESET

Thanks to higher-performance materials and improved heat treatment of the spring and adjustment system components, the wrench no longer needs to be unloaded at the end of use.

EASY SETTING

Graduated scale with added nonius allows setting of even the smallest fractions of a range, down to a tenth of an lbf.ft

GREATER VISIBILITY

Double graduated scale in lbf.ft for clearer and easier torque visibility.

Dimensions





Certifications and Standards



UNI EN ISO 6789

Coded items

	Art.	lbf.ft	■	D mm	A mm	L mm	g	
006660762	666 LBF.FT/2	4÷18	1/4	26	25	273	395	0,05
006660763	666 LBF.FT/2X	4÷18	3/8	26	29	273	405	0,05
006660765	666 LBF.FT/5	7÷37	3/8	30	33	342	680	0,25
006660780	666 LBF.FT/10	15÷75	3/8	30	33	385	760	0,25
006660781	666 LBF.FT/10X	15÷75	1/2	30	37	385	770	0,25
006660782	666 LBF.FT/20	30÷150	1/2	42	43	471	1020	0,5
006660783	666 LBF.FT/30	50÷230	1/2	42	43	600	1270	1,0

Scan the QR Code to access the web tab

Specs, media and documentation in one click.

