

666 LBF.FT

ZERO-RESET click-type wrench, scale in lbf.ft



UNI EN ISO 6789

The wrench that does not require releasing tension after use. 100% Italian-made, it is ideal for controlled tightening of screws/bolts.

ZERO-RESET TECHNOLOGY: Based on higher-performance materials and improved heat treatment of both the spring and the component parts of the adjustment system, the wrench no longer requires releasing tension after use.

EASY SETTINGS: The graduated vernier scale allows minimum interval fractions to be set up (in tenths of lbf.ft).

IMPROVED VISIBILITY: Double graduation in Nm for clearer, simpler torque visibility.

100% ITALIAN-MADE: Entirely designed and manufactured in Italy, assembled, tested and certified at Beta's Dynalab, at our headquarters in Sovico, which translates into top-quality torque wrenches.

WIDE RANGE: The range comprising 7 wrenches allows tightening from 4 to 230 lbf.ft, with 1/4" to 1/2" male square drives.

REVERSIBLE RATCHET: 72 tooth mechanism, for quick, accurate wrench operation, ensuring a take-up angle of no more than 5°. Ideal for right-hand tightening; torque accuracy: $\pm 3\%$

DOUBLE GRADUATION: High scale visibility. Easy-to-select settings, with extremely accurate increments.

BI-MATERIAL HANDLE: Ergonomic handle, for a safe, comfortable hold. Made from materials resistant to fuel, oil and industrial liquids.

TORQUE LOCKING PUSH-PULL SYSTEM: Lock/release knob with high-visibility red ring in released position. Torque is set by rotating the handle.

CLICK MECHANISM: The mechanical click can be heard and touched.

ZERO-RESET TECHNOLOGY: Based on the new parts, the wrench no longer has to be reset to the minimum value at the end of the operation cycle.



	art.	art.
	006660762	666 LBF.FT/2
	006660763	666 LBF.FT/2X
	006660765	666 LBF.FT/5
	006660780	666 LBF.FT/10
	006660781	666 LBF.FT/10X
	006660782	666 LBF.FT/20
	006660783	666 LBF.FT/30