



- Se puede utilizar como herramienta de percusión con mazos o martillos neumáticos



		art.					g
★	000780327	78AS 1.1/16	1.1/16	180	47,0	16,0	270
★	000780329	78AS 1.1/8	1.1/8	190	52,0	17,0	370
★	000780330	78AS 1.3/16	1.3/16	190	52,0	17,0	370
★	000780332	78AS 1.1/4	1.1/4	197	55,0	20,0	380
★	000780333	78AS 1.5/16	1.5/16	197	55,0	20,0	410
★	000780335	78AS 1.3/8	1.3/8	223	66,0	22,0	410
★	000780336	78AS 1.7/16	1.7/16	223	66,0	22,0	660
★	000780338	78AS 1.1/2	1.1/2	223	66,0	22,0	640
★	000780341	78AS 1.5/8	1.5/8	223	66,0	22,0	800
★	000780343	78AS 1.11/16	1.11/16	225	66,0	20,5	800
★	000780346	78AS 1.13/16	1.13/16	240	75,0	22,5	980
★	000780348	78AS 1.7/8	1.7/8	250	80,0	27,0	985
★	000780350	78AS 2	2	250	80,0	27,0	1100
★	000780352	78AS 2.1/16	2.1/16	250	80,0	27,0	1100
★	000780355	78AS 2.3/16	2.3/16	275	90,0	27,0	1430
★	000780360	78AS 2.3/8	2.3/8	270	93,5	26,0	1610
★	000780365	78AS 2.9/16	2.9/16	302	104,0	32,0	2050
★	000780370	78AS 2.3/4	2.3/4	350	120,0	35,0	2540
★	000780375	78AS 2.15/16	2.15/16	350	120,0	35,0	2800
★	000780380	78AS 3.1/8	3.1/8	354	127,0	39,0	3350