

**DIN 580:2018-04**
**TECHNISCHE DATA**


- Veiligheids factor: 6
- Hittebehandeling: genormaliseerd
- Identificatie code

**LABORATORIUM TESTS**


- Chemische analyse
- Metalgrafische analyse
- Treksterkte test

**VERKRIJGBARE CERTIFICATEN**

- Technische product specificaties
- Test rapport UNI EN10204 type 2.2
- Inspectie certificaat UNI EN10204 type 3.1
- CE conformiteits verklaring



WLL

		art.				E mm	
	080409606	8040EZ-4K M6	M6				4
	080409608	8040EZ-4K M8	M8				4
	080409610	8040EZ-2K M10	M10				2
	080409412	8040EZ-K M12	M12	1,75	340	20,5	1
*	080409414	8040EZ-K M14	M14	2	480	20,5	1
	080409416	8040EZ-K M16	M16	2	700	27	1
*	080409418	8040EZ-K M18	M18	2,5	930	27	1
	080409420	8040EZ-K M20	M20	2,5	1200	30	1
*	080409422	8040EZ-K M22	M22	2,5	1450	30	1
	080409424	8040EZ-K M24	M24	3	1800	36	1
*	080409427	8040EZ-K M27	M27	3	2400	41	1
	080409430	8040EZ-K M30	M30				1