

**8041 Lifting eyebolts, high-tensile alloy steel**

CE

**TECHNICAL DATA**

- safety factor: 4
- heat treatment: hardening and tempering

• traceability code


**LABORATORY TESTS**

- chemical analysis
- metallographic analysis
- tensile test
- fatigue test (20,000 cycles)
- proof load test (100% of batch)

**AVAILABLE CERTIFICATES**

- Technical product specifications
- Test report UNI EN10204 type 2.2
- Inspection certificate UNI EN10204 type 3.1
- CE Declaration of Conformity



		art.				WLL kg
	<b>080410206</b>	8041HP M6	M6	1	11	400
*	<b>080410208</b>	8041 M8	M8	1,25	13	800
*	<b>080410210</b>	8041 M10	M10	1,5	17	1000
*	<b>080410212</b>	8041 M12	M12	1,75	20,5	1600
	<b>080410214</b>	8041HP M14	M14	2	20,5	3000
	<b>080410217</b>	8041HP M16	M16	2,5	27	4000
	<b>080410218</b>	8041HP M18	M18	2,5	27	5000
	<b>080410221</b>	8041HP M20	M20	3,0	30	6000
	<b>080410222</b>	8041HP M22	M22	2,5	30	7000
	<b>080410225</b>	8041HP M24	M24	3	36	8000
	<b>080410227</b>	8041HP M27	M27	3	41	10000
*	<b>080410230</b>	8041 M30	M30	3,5	45	12000