

8049V Lifting eyebolts with offset brackets, high-tensile alloy steel

CE

- 360° swivel eyebolt and swivel bracket, recommended for pulling (at a 90° degree angle) and lashing loads.
- When not in use, swivel bracket can be moved as far as required to touch support, thus resulting in a more compact accessory
- With spring, for holding bracket in position, thus reducing vibration and noise of accessory when not in use.
- Designed for over 20,000 full-load work cycles.
- Test load applied to 100% of pieces before sale.



TECHNICAL DATA

- safety factor: 4
- heat treatment: hardening and tempering
- traceability code

LABORATORY TESTS

- chemical analysis
- metallographic analysis
- tensile test
- fatigue test (20,000 cycles)
- test load (100% of batch)

AVAILABLE CERTIFICATES

- Technical product specifications
- Test report UNI EN10204 type 2.2
- Inspection certificate UNI EN10204 type 3.1
- CE Declaration of Conformity

art.	art.	Ø mm	E mm	B mm	WLL kg
080490312	8049V M12-18	M12	18	37,5	1000
080490316	8049V M16-24	M16	24	37,5	1500
080490320	8049V M20-35	M20	35,5	54	2500
080490324	8049V M24-35	M24	35,5	54	4000
080490310	8049V M10-13	M10	13,5	37	630