ROBUR 8090R

lifting connecting links alloy steel, painted

The Robur Grade 8 range of accessories is made of high-tensile steel and is suitable for intensive and continuous safe use.

Designed in accordance with European technical standard EN1677-1, ROBUR quick links allow the assembly of pendants in compliance with the requirements of standard EN818-4 and compliance with Legislative Decree 81.



Certifications and Standards:

CE EN 1677-1

Features

Designed in accordance with European technical standards, Robur Grade 8 accessories are 100% load tested.

WORKING LOAD AND DURABILITY

High-tensile alloy steel allows high mechanical performance and ensures a long service life.

SUITABLE FOR HEAVY-DUTY USE

Designed to withstand over 20,000 work cycles at full load, they are suitable for continuous and repeated use at maximum capacity.

WIDE TEMPERATURE RANGE OF USE


The quality of the materials used allows them to be used at both low and high temperatures (-40°/+200°) without any change in mechanical and performance characteristics.

ROBUR 8090R

lifting connecting links alloy steel, painted

Technical Specifications

Dimensions



Certifications and Standards:

CE EN 1677-1

Coded items

	Art.		WLL kg	Ø mm	ØC max	A mm
080900111	8090R 1,12		1120	6	13	7,5
080900115	8090R 1,5		1500	7	18	9
080900120	8090R 2,0		2000	8	18	11
080900131	8090R 3,15		3150	10	22	13,0
080900153	8090R 5,3	lifting connecting links alloy steel, painted	5300	13	30	16
080900180	8090R 8,0		8000	16	32	22
080900312	8090R 12,5		12500	20	40	25

Scan the QR Code to access the web tab

Specs, media and documentation in one click.