



**ROBUR 8094SL/G10**  
lifting chain slings, 4 legs,  
self-locking hook, grade 10



**Certifications and Standards**



**Features**

A combination of safety, efficiency, and durability that makes them particularly suitable for lifting operations in industry.

**INCREASED LOAD CAPACITY**

High-strength alloy steels allow high mechanical performance compared to Grade 8 accessories.

**SUITABLE FOR HEAVY-DUTY USE**

Designed to support more than 20,000 working cycles at full load, they are suitable for continuous and repeated use at maximum capacity.

**WEAR-RESISTANT**

They are less susceptible to wear and deformation; they therefore have a longer service life, reducing the need for replacement.

**OPERATIONAL EFFICIENCY**

Compared to grade 8, grade 10 chain slings, with the same load capacity, weigh on average 30% less, facilitating manoeuvrability and installation.



## Dimensions



CE

## Certifications and Standards

## Coded items

	Art.	 D mm	L m	WLL ton
080941201	8094SL/G10 D6-1	6*	1	3
080941202	8094SL/G10 D6-2	6*	2	3
080941203	8094SL/G10 D6-3	6*	3	3
080941204	8094SL/G10 D6-4	6*	4	3
080941241	8094SL/G10 D8-1	8*	1	5,3
080941242	8094SL/G10 D8-2	8*	2	5,3
080941243	8094SL/G10 D8-3	8*	3	5,3
080941244	8094SL/G10 D8-4	8	4	5,3
080941251	8094SL/G10 D10-1	10*	1	8
080941252	8094SL/G10 D10-2	10	2	8
080941253	8094SL/G10 D10-3	10	3	8
080941254	8094SL/G10 D10-4	10	4	8
080941331	8094SL/G10 D13-1	13	1	14
080941332	8094SL/G10 D13-2	13	2	14
080941333	8094SL/G10 D13-3	13	3	14
080941334	8094SL/G10 D13-4	13	4	14

**Scan the QR Code to access the web tab**

Specs, media and documentation in one click.

