

8150
Hebebänder, 1t, veilchenfarben, doppellagig, verstärkte Längslöcher, aus hochfestem Polyester (PES)

CE

EN 1492-1



	art.	L m	H mm	WLL ton
081500005	8150 0,5-T1	0,5	30	1
081500010	8150 1-T1	1	30	1
081500015	8150 1,5-T1	1,5	30	1
081500020	8150 2-T1	2	30	1
081500025	8150 2,5-T1	2,5	30	1
081500030	8150 3-T1	3	30	1
081500035	8150 3,5-T1	3,5	30	1
081500040	8150 4-T1	4	30	1
081500050	8150 5-T1	5	30	1
081500060	8150 6-T1	6	30	1
081500080	8150 8-T1	8	30	1

				$\beta = 0^\circ + 45^\circ$	$\beta = 45^\circ + 60^\circ$
30	1 t	0,6 t	2 t	1,4 t	1 t
60	2 t	1,6 t	4 t	2,8 t	2 t
90	3 t	2,4 t	6 t	4,2 t	3 t
120	4 t	3,2 t	8 t	5,6 t	4 t
150	5 t	4,0 t	10 t	7,0 t	5 t
180	6 t	4,8 t	12 t	8,4 t	6 t
240	8 t	6,4 t	16 t	11,2 t	8 t
300	10 t	8,0 t	20 t	14,0 t	10 t