

8157

**zvedací pásy, šedé 4t dvouvrstvé se zesílenými oky vysokozátěžový pás z polyesteru (PES)**

CE

EN 1492-1



| art.      | L<br>m | H<br>mm | WLL<br>ton |
|-----------|--------|---------|------------|
| 081570020 | 2      | 120     | 4          |
| 081570030 | 3      | 120     | 4          |
| 081570040 | 4      | 120     | 4          |
| 081570050 | 5      | 120     | 4          |
| 081570060 | 6      | 120     | 4          |
| 081570080 | 8      | 120     | 4          |
| 081570100 | 10     | 120     | 4          |
| 081570120 | 12     | 120     | 4          |

|     |     |      |     | $\beta=0^{\circ}+45^{\circ}$ | $\beta=45^{\circ}+60^{\circ}$ |
|-----|-----|------|-----|------------------------------|-------------------------------|
| 30  | 1t  | 0,8t | 2t  | 1,4t                         | 1t                            |
| 60  | 2t  | 1,6t | 4t  | 2,8t                         | 2t                            |
| 90  | 3t  | 2,4t | 6t  | 4,2t                         | 3t                            |
| 120 | 4t  | 3,2t | 8t  | 5,6t                         | 4t                            |
| 150 | 5t  | 4,0t | 10t | 7,0t                         | 5t                            |
| 180 | 6t  | 4,8t | 12t | 8,4t                         | 6t                            |
| 240 | 8t  | 6,4t | 16t | 11,2t                        | 8t                            |
| 300 | 10t | 8,0t | 20t | 14,0t                        | 10t                           |