



ROBUR 8170

lifting round slings, purple 1t high-tenacity polyester (PES) belt

	0	1	2	3
	1t	2t	3t	4t
	1.0t	2.0t	3.0t	4.0t
	1.1t	2.2t	3.3t	4.4t
	1.2t	2.4t	3.6t	4.8t
	1.3t	2.6t	3.9t	5.2t
	1.4t	2.8t	4.2t	5.6t
	1.5t	3.0t	4.5t	6.0t
	1.6t	3.2t	4.8t	6.4t
	1.7t	3.4t	5.1t	6.8t
	1.8t	3.6t	5.4t	7.2t
	1.9t	3.8t	5.7t	7.6t
	2.0t	4.0t	6.0t	8.0t

Certifications and Standards



EN 1492-2

HIGH-TENACITY POLYESTER BELT

High-tenacity polyester offers weather resistance and excellent long-term stability. It has good resistance to acids, solvents and microorganisms and retains the same characteristics dry and wet.

VERSATILITY OF USE

Easy and quick to handle, they have an internal hank of parallel polyester threads, free to adapt to the surface of irregularly shaped loads, reducing slipping and sliding.

TRACKABILITY

The label, made of tear-resistant material, is wrapped in transparent PVC protection and bears the manufacturer's name, load capacity, CE marking, batch code and serial marking.

This label is often subject to wear and tear during use, and if the data are erased or the label is cut and lost, the

RANGE WIDTH AND COLOUR CODE

Available in multiple lengths and tonnages, the belt's colour code immediately identifies the working load limit; as well as the number of lines along the length of the sheath indicating its load capacity in tonnes.

Dimensions




CE

Certifications and Standards

EN 1492-2

Coded items

	Art.	L m	WLL ton	H mm
081700010	8170 0,5-T1	0,5	1	45
081700020	8170 1-T1	1	1	45
081700030	8170 1,5-T1	1,5	1	45
081700040	8170 2-T1	2	1	45
081700050	8170 2,5-T1	2,5	1	45
081700060	8170 3-T1	3	1	45
081700080	8170 4-T1	4	1	45
081700100	8170 5-T1	5	1	45

Scan the QR Code to access the web tab

Specs, media and documentation in one click.

