



ROBUR 8173

lifting round slings, green 2t high-tenacity polyester (PES) belt

	0	1	2	3
	1t	2t	3t	4t
	1.0t	2.0t	3.0t	4.0t
	1.1t	2.2t	3.3t	4.4t
	1.2t	2.4t	3.6t	4.8t
	1.3t	2.6t	3.9t	5.2t
	1.4t	2.8t	4.2t	5.6t
	1.5t	3.0t	4.5t	6.0t
	1.6t	3.2t	4.8t	6.4t
	1.7t	3.4t	5.1t	6.8t
	1.8t	3.6t	5.4t	7.2t
	1.9t	3.8t	5.7t	7.6t
	2.0t	4.0t	6.0t	8.0t

Certifications and Standards



EN 1492-2

HIGH-TENACITY POLYESTER BELT

High-tenacity polyester offers weather resistance and excellent long-term stability. It has good resistance to acids, solvents and microorganisms and retains the same characteristics dry and wet.

VERSATILITY OF USE

Easy and quick to handle, they have an internal hank of parallel polyester threads, free to adapt to the surface of irregularly shaped loads, reducing slipping and sliding.

TRACKABILITY

The label, made of tear-resistant material, is wrapped in transparent PVC protection and bears the manufacturer's name, load capacity, CE marking, batch code and serial marking. This label is often subject to wear and tear during use, and if the data are erased or the label is cut and lost, the band must be replaced: the additional PVC protection

RANGE WIDTH AND COLOUR CODE

Available in multiple lengths and tonnages, the belt's colour code immediately identifies the working load limit; as well as the number of lines along the length of the sheath indicating its load capacity in tonnes.

Dimensions




CE

Certifications and Standards

EN 1492-2

Coded items

	Art.	L m	WLL ton	H mm
081730010	8173 0,5-T2	0,5	2	50
081730020	8173 1-T2	1	2	50
081730030	8173 1,5-T2	1,5	2	50
081730040	8173 2-T2	2	2	50
081730050	8173 2,5-T2	2,5	2	50
081730060	8173 3-T2	3	2	50
081730080	8173 4-T2	4	2	50
081730100	8173 5-T2	5	2	50
081730120	8173 6-T2	6	2	50
081730160	8173 8-T2	8	2	50

Scan the QR Code to access the web tab

Specs, media and documentation in one click.

