










**8176**
**cables redondos de anillo, 3t, amarillo, tejido en poliéster de alta tenacidad (PES)**

CE

EN 1492-2



| art.      | art.        |     |   |    |
|-----------|-------------|-----|---|----|
| 081760010 | 8176 0,5-T3 | 0,5 | 3 | 60 |
| 081760020 | 8176 1-T3   | 1   | 3 | 60 |
| 081760030 | 8176 1,5-T3 | 1,5 | 3 | 60 |
| 081760040 | 8176 2-T3   | 2   | 3 | 60 |
| 081760050 | 8176 2,5-T3 | 2,5 | 3 | 60 |
| 081760060 | 8176 3-T3   | 3   | 3 | 60 |
| 081760080 | 8176 4-T3   | 4   | 3 | 60 |
| 081760100 | 8176 5-T3   | 5   | 3 | 60 |
| 081760120 | 8176 6-T3   | 6   | 3 | 60 |
| 081760160 | 8176 8-T3   | 8   | 3 | 60 |

|   |  |  |  |  |
|---|---|---|---|---|
|    | 1t  | 0,8t  | 2t  | 1,4t  |
|    | 2t  | 1,6t  | 4t  | 2,8t  |
|    | 3t  | 2,4t  | 6t  | 4,2t  |
|   | 4t  | 3,2t  | 8t  | 5,6t  |
|  | 5t  | 4,0t  | 10t   | 7,0t  |