

**920INOX-A**
**Chiavi a bussola con attacco quadro femmina 1/2" bocca esagonale, in acciaio inossidabile**

**DIN 3124 - UNI ISO 2725**

- elevata resistenza alla corrosione
- evita la ruggine impropria
- ottime caratteristiche meccaniche
- acciaio inossidabile AISI 420

|                  | art.         | mm | mm | mm | mm | mm | mm   | g   |
|------------------|--------------|----|----|----|----|----|------|-----|
| <b>009203008</b> | 920INOX-A 8  | 8  | 15 | 10 | 40 | 24 | 14,0 | 77  |
| <b>009203009</b> | 920INOX-A 9  | 9  | 16 | 10 | 40 | 24 | 14,0 | 78  |
| <b>009203010</b> | 920INOX-A 10 | 10 | 17 | 10 | 40 | 24 | 15,0 | 78  |
| <b>009203011</b> | 920INOX-A 11 | 11 | 18 | 11 | 40 | 24 | 15,0 | 79  |
| <b>009203012</b> | 920INOX-A 12 | 12 | 19 | 11 | 40 | 24 | 15,0 | 79  |
| <b>009203013</b> | 920INOX-A 13 | 13 | 20 | 11 | 40 | 24 | 15,0 | 80  |
| <b>009203014</b> | 920INOX-A 14 | 14 | 21 | 11 | 40 | 24 | 16,5 | 80  |
| <b>009203015</b> | 920INOX-A 15 | 15 | 23 | 11 | 40 | 25 | 16,5 | 94  |
| <b>009203016</b> | 920INOX-A 16 | 16 | 24 | 11 | 40 | 25 | 16,5 | 94  |
| <b>009203017</b> | 920INOX-A 17 | 17 | 25 | 11 | 40 | 25 | 17,5 | 94  |
| <b>009203018</b> | 920INOX-A 18 | 18 | 26 | 13 | 42 | 25 | 18,8 | 94  |
| <b>009203019</b> | 920INOX-A 19 | 19 | 28 | 13 | 42 | 25 | 21,5 | 110 |
| <b>009203020</b> | 920INOX-A 20 | 20 | 29 | 13 | 42 | 26 | 21,5 | 120 |
| <b>009203021</b> | 920INOX-A 21 | 21 | 30 | 13 | 43 | 26 | 21,5 | 125 |
| <b>009203022</b> | 920INOX-A 22 | 22 | 31 | 15 | 43 | 26 | 22,6 | 130 |
| <b>009203024</b> | 920INOX-A 24 | 24 | 34 | 15 | 43 | 28 | 22,7 | 165 |
| <b>009203027</b> | 920INOX-A 27 | 27 | 38 | 18 | 46 | 30 | 22,7 | 215 |
| <b>009203030</b> | 920INOX-A 30 | 30 | 42 | 20 | 46 | 30 | 22,7 | 250 |
| <b>009203032</b> | 920INOX-A 32 | 32 | 44 | 20 | 46 | 34 | 25,3 | 295 |

