



UNI 6742 DIN 3112

- Sliding handle can be stopped in required position throughout length.
- A safety catch prevents handle from coming out, thereby avoiding accidents.
- Triple size marking on head.

	art.	⌀ mm	L mm	∅ mm	L1 mm	A mm	A1 mm	⚖ g
009500006	950 6	6	210	10,1	145	5,0	16,0	98
009500007	950 7	7	212	11,2	145	6,0	18,0	100
009500008	950 8	8	220	12,4	160	7,0	19,0	140
009500009	950 9	9	223	13,5	160	8,0	20,0	142
009500010	950 10	10	230	14,9	160	8,5	21,0	172
009500011	950 11	11	233	16,1	160	9,0	22,0	176
009500012	950 12	12	240	17,5	175	9,5	23,0	228
009500013	950 13	13	244	19,7	175	10,5	24,0	233
009500014	950 14	14	250	20,1	190	11,5	25,0	289
009500015	950 15	15	254	21,5	190	12,0	25,0	307
009500016	950 16	16	260	22,7	200	12,5	26,0	414
009500017	950 17	17	264	24,1	200	13,0	27,0	436
009500019	950 19	19	274	26,6	230	14,5	29,0	553
009500022	950 22	22	290	29,9	290	16,0	32,0	797
009500024	950 24	24	300	32,2	320	18,0	36,0	976
009500027	950 27	27	315	36,2	370	21,0	42,0	1265

