


UNI 6754

- Swivelling mechanism allows hexagon male end pre-positioning at an angle of up to 50°.
- Reduce tightening effort to 90° in fixed position during use.
- Hexagon bar can be stopped in required position throughout length; a safety catch prevents bar from coming out.

| art. | mm | L mm | L1 mm | Ø mm | H mm | g | |
|-----------|---------|------|-------|------|------|----|-----|
| 009530130 | 953 3 | 3 | 395 | 145 | 12,5 | 5 | 162 |
| 009530135 | 953 3,5 | 3,5 | 395 | 145 | 12,5 | 6 | 161 |
| 009530140 | 953 4 | 4 | 395 | 145 | 12,5 | 6 | 163 |
| 009530145 | 953 4,5 | 4,5 | 395 | 145 | 12,5 | 7 | 162 |
| 009530150 | 953 5 | 5 | 395 | 145 | 12,5 | 7 | 163 |
| 009530160 | 953 6 | 6 | 400 | 160 | 17 | 9 | 276 |
| 009530170 | 953 7 | 7 | 425 | 175 | 19 | 10 | 370 |
| 009530180 | 953 8 | 8 | 425 | 175 | 19 | 11 | 370 |
| 009530200 | 953 10 | 10 | 440 | 200 | 22 | 13 | 578 |

