

9803H
threadlocker-High Resistance

Ideal for permanent locking of parts that do not need subsequent dismantling, and for passivated metal surfaces, including brass, aluminium and stainless steel. Does not allow disassembly with hand tools.

Features:

- Anaerobic threadlocker for metal threads
- Prevents screws, bolts and studs from loosening due to vibrations and shocks
- Polymerizes in contact with ground metal parts and in absence of oxygen
- High chemical resistance (oils, water, gas, etc.)
- Protects threads from corrosion and seizure from corrosion
- Ideal for all threaded metal joints
- Available in 3 strength classes

Temperature range (°C)	-50/+150
Max gap fill (mm)	0,25
Handling cure time (minutes)	10/15
Functional cure time (h)	3-6
Viscosity (mPa.s) 25°C	800/1200
Breakaway torque ISO-10964	35-45 Nm
Prevailing torque ISO-10964	30-40 Nm

	art.	Confezione	Formato mL
098030002	9803H 20 (1-2)	bottle	20
098030005	9803H 50 (1-2)	bottle	50
098030025	9803H 250 (1-2)	bottle	250
098032002	9803H 20 (3)	bottle	20
098032005	9803H 50 (3)	bottle	50
098032025	9803H 250 (3)	bottle	250

