

**9812M**
**thread sealant-Medium Resistance**

Ideal for sealing nipples parts subject to periodic maintenance.  
 Allows dismantling by using hand tools.

Anaerobic thread sealant for threaded metal joints. Provides perfect tightness to liquids and gases.

Makes joints sturdier.

High chemical resistance (oils, water, gas).

Tolerates slight contamination by oils

Protects threads from corrosion and seizure from corrosion.

Available in 3 strength classes.

|                              |               |
|------------------------------|---------------|
| Temperature range (°C)       | -50/+150      |
| Max gap fill (mm)            | 0,35          |
| Handling cure time (minutes) | 12/18         |
| Functional cure time (h)     | 3-6           |
| Viscosity (mPa.s) 25°C       | 20.000/40.000 |
| Breakaway torque ISO-10964   | 27-35 Nm      |
| Prevailing torque ISO-10964  | 20-30 Nm      |

| art.      | art.            |               | ml  |
|-----------|-----------------|---------------|-----|
| 098120002 | 9812M 20 (1-2)  | bottle        | 20  |
| 098120305 | 9812M S50 (1-2) | bellow bottle | 50  |
| 098120505 | 9812M T50 (1-2) | tube          | 50  |
| 098120525 | 9812M T250      | tube          | 250 |
| 098122002 | 9812M 20 (3)    |               | 20  |
| 098122305 | 9812M S50 (3)   |               | 50  |
| 098122505 | 9812M T50 (3)   |               | 50  |
| 098122525 | 9812M T250 (3)  |               | 250 |

