

9813H

## thread sealant-High Resistance

Ideal for permanent sealing of nipples, that do not need subsequent dismantling, and for passivated metal surfaces, including brass, aluminium and stainless steel. Does not allow disassembly with hand tools.

Anaerobic thread sealant for threaded metal joints. Provides perfect tightness to liquids and gases.

Makes joints sturdier.

High chemical resistance (oils, water, gas).

Tolerates slight contamination by oils

Protects threads from corrosion and seizure from corrosion.

Available in 3 strength classes.

Temperature range (°C)	-50/+200
Max gap fill (mm)	0,15
Handling cure time (minutes)	10/15
Functional cure time (h)	3-6
Viscosity (mPa.s) 25°C	40.000/80.000
Breakaway torque ISO-10964	35-45 Nm
Prevailing torque ISO-10964	25-35 Nm

art.	art.	Confezione	Formato mL
098130002	9813H 20 (1-2)	bottle	20
098130505	9813H T50 (1-2)	tube	50
098130305	9813H S50 (1-2)	bellow bottle	50
098130525	9813H T250	tube	250
098132002	9813H 20 (3)	bottle	20
098132305	9813H S50 (3)	bellow bottle	50
098132505	9813H T50 (3)	tube	50
098132525	9813H T250 (3)	tube	250

