


9822M
liquid gasket-Medium Resistance

Ideal for sealing of surfaces of parts subject to periodic maintenance
 Allows dismantling by using hand tools.

Anaerobic liquid gasket, ideal for flat mating of ground metal surfaces.
 Prevents loosening of joints and bolts and changes in thickness.
 High chemical and thermal resistance (oils, water, gas).
 Available in 3 strength classes.

| | |
|------------------------------|---------------|
| Temperature range (°C) | -50/+150 |
| Max gap fill (mm) | 0,35 |
| Handling cure time (minutes) | 10/15 |
| Functional cure time (h) | 3-6 |
| Viscosity (mPa.s) 25°C | 40.000/70.000 |
| Breakaway torque ISO-10964 | 25-35 Nm |
| Prevailing torque ISO-10964 | 20-30 Nm |



|  | art. | Confezione | Formato mL |
|---|-----------------|---------------|------------|
| 098220002 | 9822M 20 (1-2) | bottle | 20 |
| 098220305 | 9822M S50 (1-2) | bellow bottle | 50 |
| 098220505 | 9822M T50 (1-2) | tube | 50 |
| 098220525 | 9822M T250 | tube | 250 |
| 098222002 | 9822M 20 (3) | bottle | 20 |
| 098222305 | 9822M S50 (3) | bellow bottle | 50 |
| 098222505 | 9822M T50 (3) | tube | 50 |
| 098222525 | 9822M T250 (3) | tube | 250 |