9823H liquid gasket-High Resistance

Ideal for permanent sealing of surfaces. Also ideal for reclaiming bearing housings and worn parts.
Does not allow disassembly with hand tools.

Anaerobic liquid gasket, ideal for flat mating of ground metal surfaces.
Prevents loosening of joints and bolts and changes in thickness.
High chemical and thermal resistance (oils, water, gas).
Available in 3 strength classes.

Temperature range (°C)	**-50/+150**
Max gap fill (mm)	0,35
Handling cure time (minutes)	**10/16**
Functional cure time (h)	3-6
Viscosity (mPa.s) 25°C	**100.000/200.000**
Breakaway torque ISO-10964	35-45 Nm
Prevailing torque ISO-10964	**20-30 Nm**

	Art.	Packaging	Format ml
098230002	9823H 20 (1-2)	bottle	20
098230505	9823H T50 (1-2)	tube	50
098230305	9823H S50 (1-2)	bellow bottle	50
098230525	9823H T250 (1-2)	tube	250
098232002	9823H 20 (3)	bottle	20
098232305	9823H S50 (3)	bellow bottle	50
098232505	9823H T50 (3)	tube	50
098232525	9823H T250 (3)	tube	250











Scan the QR Code to access the web tab
Specs, media and documentation in one click.