

9823H
liquid gasket-High Resistance

Ideal for permanent sealing of surfaces. Also ideal for reclaiming bearing housings and worn parts.

Does not allow disassembly with hand tools.

Anaerobic liquid gasket, ideal for flat mating of ground metal surfaces.

Prevents loosening of joints and bolts and changes in thickness.

High chemical and thermal resistance (oils, water, gas).

Available in 3 strength classes.

| | |
|------------------------------|-----------------|
| Temperature range (°C) | -50/+150 |
| Max gap fill (mm) | 0,35 |
| Handling cure time (minutes) | 10/16 |
| Functional cure time (h) | 3-6 |
| Viscosity (mPa.s) 25°C | 100.000/200.000 |
| Breakaway torque ISO-10964 | 35-45 Nm |
| Prevailing torque ISO-10964 | 20-30 Nm |

| part number | art. | | ml |
|-------------|-----------------|---------------|-----|
| 098230002 | 9823H 20 (1-2) | bottle | 20 |
| 098230505 | 9823H T50 (1-2) | tube | 50 |
| 098230305 | 9823H S50 (1-2) | bellow bottle | 50 |
| 098230525 | 9823H T250 | tube | 250 |
| 098232002 | 9823H 20 (3) | | 20 |
| 098232305 | 9823H S50 (3) | | 50 |
| 098232505 | 9823H T50 (3) | | 50 |
| 098232525 | 9823H T250 (3) | | 250 |

